

FLANGE ALIGNMENT PINS



Safe, fast, and effective solution for even the toughest flange alignment jobs. The tool's tapered shaft is a feature that eliminates the need for hammering and prying when lining up flange bolt holes. Flange aligning pins are made of steel and surface coated for rust protection and marked with both the bolt hole size and part number for easy identification.

Features

- Sold individually or in sets: sizes range from 1/2" to 2.5/8" hole diameter. The only flange alignment pin on the market that compensates for up, down and rotational misalignment.
- Flange alignment pins are made from 4140 heat treated steel and are then black oxide coated for corrosion resistance.
- Flange aligning pins are available in individually and in sets.
- Also available in extra 'L' versions (Extra Long).

Bolt Hole Size inch	Model No.	Standard Length inch	Weight kg	Model No.	Extra Long Length inch	Weight kg
1/2"	FP-0.08	2.3/8"	0.06	FP-0.08L	5.3/8"	0.28
5/8"	FP-0.10	2.3/4"	0.11	FP-0.10L	5.3/4"	0.34
3/4"	FP-0.12	3.1/4"	0.20	FP-0.12L	6.1/4"	0.40
7/8"	FP-0.14	3.1/2"	0.31	FP-0.14L	6.1/2"	0.51
1"	FP-1.00	4"	0.45	FP-1.00L	7"	0.68
1.1/8"	FP-1.02	5"	0.68	FP-1.02L	8"	1.02
1.1/4"	FT-1.04	5.1/2"	0.91	FT-1.04L	8.1/2"	1.36
1.3/8"	FP-1.06	6.1/4"	1.30	FP-1.06L	9.1/4"	1.81
1.1/2"	FP-1.08	6.1/2"	1.47	FP-1.08L	9.1/2"	3.00
1.5/8"	FP-1.10	7.1/4"	1.87	FP-1.10L	10.1/4"	2.61
1.3/4"	FP-1.12	7.7/8"	2.15	FP-1.12L	10.7/8"	3.18
1.7/8"	FP-1.14	8.3/8"	3.18	FP-1.14L	11.3/8"	3.69
2"	FP-2.00	9"	3.01	FP-2.00L	12"	4.20
2.1/8"	FP-2.02	12"	4.88	FP-2.02L	15"	6.12
2.3/8"	FP-2.06	13.1/4"	6.12	FP-2.06L	16.1/4"	8.16
2.5/8"	FP-2.10	14"	7.71	FP-2.10L	17"	9.53

2 of Each Size inch	Set with case		Extra Long - Set with case	
	Model No.	Weight kg	Model No.	Weight kg
3/4", 7/8", 1"	FPS-01	3.63	FPS-01L	5.89
3/4", 7/8", 1", 1.1/8"	FPS-02	4.99	FPS-02L	8.16
3/4", 7/8", 1", 1.1/8", 1.1/4"	FPS-03	6.80	FPS-03L	9.52
3/4", 7/8", 1", 1.1/8", 1.1/4", 1.3/8"	FPS-04	9.98	FPS-04L	14.51