

HIGH PRESSURE ACCESSORIES

High Pressure Tensioner Hoses :

High Pressure Tensioner Hoses for various tensioning applications are available in different lengths and end-fittings:



Hose Reel



Lead Hose



Connecting Hose

Features :

- 4- Ply construction.
- Available in 1.5m, 3m and 5m standard lengths. Other custom built lengths also available.
- Max. Working Pressure : 1800 Bar.
- Burst Pressure : 4500 Bar.
- Min. Bend Radius : 150mm
- All hoses fitted with quick connect Couplings at both ends.
- Working Temperature Range: -30 to 80 Deg C.
- Tensioner Hose Reel of upto 500m single hose for sub sea applications available with required end fittings.

Part No.	OAL Mtr.	QRC
PU-HG-0150	1.5	F X F
PU-HG-0300	3.0	F x F
PU-HG-0300-L	3.0	F x M
PU-HG-0500	5.0	F x F
PU-HG-0500-L	5.0	F x M

Manifolds, Fittings and Couplings :

Manifolds, Fittings and Couplings of various configurations are available for all tensioning applications:



Couplings



Fittings



Manifolds

Features :

- Manifold /Blocks for 1500 working pressure.
- T-Fittings for 1500 Bar working pressure.
- Male / Female Couplings for 1500 and 2500 bar working pressure.
- High Pressure Fittings and Adaptors.

Part No.	Description
HCS-150-F	Coupling, 150 Mpa
HCS-150-M	Nipple, 150 Mpa
HCS-250-F	Coupling, 250 Mpa
HCS-250-F	Nipple, 250 Mpa
HF-G4-G4	Fitting, G 1/4 CS
HF-G4-M16	Fitting G 1/4 x M16