

SWA Series



These balancers are provisioned with wire arrest mechanism, which locks the drum pulley in case of tool disengagement. These balancers are available for capacity from 9 - 70 Kg. & have all the feature of SWF balancers as well. These balancers are primarily used with welding guns and applications where chances of wire slitting or tool disengagement due to accidental failure are higher.

| Model No. | Capacity kg | Travel meter | Weight kg. | Model No. | Capacity kg. | Travel meter | Weight kg. |
|-----------|-------------|--------------|------------|-----------|--------------|--------------|------------|
| SWA - 15 | 9.0 - 15.0 | 1.3 | 5.5 | SWA - 15L | 9.0 - 15.0 | 2.3 | 10.0 |
| SWA - 22 | 15.0 - 22.0 | 1.5 | 9.5 | SWA - 22L | 15.0 - 22.0 | 2.3 | 10.0 |
| SWA - 30 | 22.0 - 30.0 | 1.5 | 10.0 | SWA - 30L | 22.0 - 30.0 | 2.3 | 11.0 |
| SWA - 40 | 30.0 - 40.0 | 1.5 | 12.5 | SWA - 40L | 30.0 - 40.0 | 2.3 | 14.5 |
| SWA - 50 | 40.0 - 50.0 | 1.5 | 13.0 | SWA - 50L | 40.0 - 50.0 | 2.3 | 15.0 |
| SWA - 60 | 50.0 - 60.0 | 1.5 | 13.5 | SWA - 60L | 50.0 - 60.0 | 2.3 | 16.0 |
| SWA - 70 | 60.0 - 70.0 | 1.5 | 14.0 | SWA - 70L | 60.0 - 70.0 | 2.3 | 16.5 |