## SF-3442


## TUBE / PIPE BEVELLING AND CUTTING SPLIT FRAME MACHINE

Light and Portable Flange/Pipe BevelIng and Cutting Split Frame Machine

Locking Range 863.6mm 0D to 1066.8mm 0D (34" - 42")

Externally mounted SF-3442 is a split frame, clamshell type light and portable design. A rugged and slim machine suitable for tubes and pipes in the size range of 863.6 mm to 1066.8 mm in external diameter. It is a new generation heavy duty facing, bevelling and cutting machine designed for the Piping industry.







	Pneumatic (mm)	Electric (mm)	Hydraulic (mm)
Α	1223	1223	1223
В	1092	1092	1092
С	66	66	66
D	114	114	114

## **Features**





TRIP ASSEMBLY - It gives an auto feed to the tool bit assembly. Trip can be engaged or disengaged depending on feed required.





PNEUMATIC, ELECTRIC OR HYDRAULIC DRIVE - High quality pneumatic, electric drive or hydraulic for reliable service and long working life.

## **Technical Specification**

Drive		Pneumatic	Electric	Hydraulic
Locking Range	mm	863.6 - 1066.8	863.6 - 1066.8	863.6 - 1066.8
	(inch)	(34" - 42")	(34" - 42")	(34" - 42")
Idle Speed	rpm	10	10	9
Power Consumption	HP/Watts	4.2 HP	3.5HP/2600Watts	7.5HP(3PHASE)
Air Consumption	cfm	95	-	-
Air Pressure Bar	bar (psi)	6.2 (90)	-	100 bar
Voltage	V	-	230	415
Net Machine Weight	kg (lb)	129.0(284.0)	129.0(284.0)	129.0(284.0)
Tool Holder Weight	kg (lb)	5.0 (11.0)	5.0 (11.0)	5.0 (11.0)
Drive Weight	kg (lb)	16.0 (35.3)	23.0 (50.7)	9.0 (19.8)



▼ **SF-3442** is used for Piping industry.

**Recommended for:** 

**Tube Bevelling, Cutting, Piping Industries**