

ELECTRIC DRIVES FOR USE WITH TORQUE CONTROLLERS



MPB - 0



MPB - 1



MPG - 2



MPG - 3



Features :

- 1) Heavy Duty German motors form the heart of these drives.
- 2) Continuous cycle operation vs. Intermittent cycle operation of drives from other manufactures.
- 3) High torque to weight ratio.

SPECIFICATIONS

Supply Voltage Single Phase 50/60 Hz	Drive Model	Speed I / II	No Load R.P.M.	Expansion Range				Drive Weight Kgs.
				Steel Tube O.D.		Copper Tube O.D.		
				inch	mm	inch	mm	
230 V	MPB - 0N	I	2200	1/4" - 3/8"	6 - 10	1/4" - 1/2"	6 - 12	2
		II	1000	3/8" - 5/8"	10 - 16	3/8" - 3/4"	13 - 20	
	MPB - 1N	I	1900	5/16" - 3/8"	8 - 13	5/16" - 1/2"	8 - 13	2.5
		II	480	5/8" - 1.3/4"	16 - 45	5/8" - 2"	16 - 50	
	MPG - 2N	I	1080	5/8" - 1.1/4"	16 - 32	5/8" - 1.1/2"	16 - 38	7.5
		II	130	1" - 3"	25 - 76	1" - 4"	25 - 102	
MPG - 3N	I	430	1" - 2"	25 - 50	1" - 3"	25 - 76	8.5	
	II	430	1" - 2"	25 - 50	1" - 3"	25 - 76		
110 V	MPB - 0L	I	2200	1/4" - 3/8"	6 - 10	1/4" - 1/2"	6 - 12	2
		II	1000	3/8" - 5/8"	10 - 16	3/8" - 3/4"	13 - 20	
	MPB - 1L	I	1900	5/16" - 3/8"	8 - 13	5/16" - 1/2"	8 - 13	2.5
		II	480	5/8" - 1.3/4"	16 - 45	5/8" - 2"	16 - 50	
	MPG - 2L	I	1080	5/8" - 1.1/4"	16 - 32	5/8" - 1.1/2"	16 - 38	7.5
		II	130	1" - 3"	25 - 76	1" - 4"	25 - 102	
MPG - 3L	I	430	1" - 2"	25 - 50	1" - 3"	25 - 76	8.5	
	II	430	1" - 2"	25 - 50	1" - 3"	25 - 76		